

TRAFFIC MANAGEMENT NOTES:

- 1) All temporary traffic management shall be in accordance with Chapter 8 of the Traffic Signs Manual.
- 2) All temporary traffic management shall be in accordance with the Traffic Signs Regulations and General Directions 2016.
- 3) All temporary traffic management shall conform to the Safety at Street Works and Road Works, A Code of Practice.
- 4) All signing should be located 450mm minimum from any carriageway.
- 5) All temporary traffic management sign locations are indicative and are subject to on site approval from the Engineer.
- 6) Stop & Go boards are to be accessible and brought into operation if there is traffic signal failure.

DETAIL B (B)

Single Carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.
Single Carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.

- Notes:
- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 - 2) 45° tapers have 1.2m spacing, no relaxations.
 - 3) On motorways and all-purpose dual carriageway roads with hard shoulders on which the national speed limit applies, 'in cones' will be required for both standard works and works for which relaxations may be applied, for both lead tapers and the facing wall of a lane change.

DETAIL C1 (C1)

Single Carriageway 40mph or less - 450mm traffic cones.
Single Carriageway 50mph or more - 750mm traffic cones.

- Notes:
- 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 - 2) For relaxation to Detail C1 see Table A1.3 (Appendix 1).

SAFETY ZONE DIMENSIONS

Permanent speed limit 30mph or less
Sideway safety zone 0.5m
Longways safety zone 0.5m
(Dimensions are minimal)

Key

-  Lane closed area
-  Traffic cone
-  Traffic sign facing
-  Vehicle signal

QR Code:

Checked by:

Customer: Wales & West

Job reference: Hire Department

Location: Llwyn Y Pia Rd,
Cardiff, CF14 0SX

Date: 03.04.2024

Description: 3-Way Signals

Scale: NTS

OS HA:

Core Highways
www.corehighways.com


Produced by: Wayne MacDonald

Drawing reference: Hire Department

This Drawing is subject to Copyright and remains the property of Core Highways.
Contains Ordnance Survey data.

core
highways

Signs will be positioned on all approach roads at the distances specified
(approximate distances measured from first cone in taper)



Times for traffic signals.
All times are in seconds

Phase	1	2	3	4
Location of head	Heol Y Delyn West	Llwyn Y Pia	Heol Y Delyn East	Not in use
Red	10	10	10	0
Red/amber	2	2	2	0
Green	30	30	30	0
Amber	3	3	3	0
Phase total	45	45	45	0
Total for cycle				135